SATO

CX200TT
Thermal Transfer Printer

CX200DT
Direct Thermal Printer

- ■ **4.1″ Wide Print Area**

- ■ **3″ Per Second Print Speed**

- ■ **203 dpi Resolution**

- ■ **512K Flash Memory 512K RAM**

- ■ **Serial and Parallel Interfaces**

- ■ **2D Bar Codes**

- ■ **5″ Media Roll**

- ■ **User Replaceable Print Head and Platen**

- ■ **High Lift Print Head for Easy Loading/Cleaning**

- ■ **Ready-To-Go Complete Labeling Package**

The CX200 reflects the innovative design and reliability that has become synonymous with the SATO name. Like other SATO printers, the CX200 also uses the SATO Command Language. This means you can simply add any printer into existing applications, combining the level and capability of the various SATO printer models to meet your changing needs.

The portability and compact design of the CX200 allow it to fit in anywhere - on a crowded work surface or at a busy warehouse, distribution center, or at points of transaction… even on your desk next to your computer.

Designed for ease of use, the CX200 can print over 2200 1" labels from a 5" roll of label media. And in the thermal transfer model, a 5500" ribbon roll allows a convenient 2 to 1 ratio between the media and ribbon, simplifying your media supply management. Also, the high lift print head carriage allows for easy loading and maintenance. These and other advanced features make the CX200 printer the best in the desktop labeling category and lead the way in convenience and easy printing!

Backed by SATO's world class reputation for reliability, the CX200 is the ideal printer for the cost-conscious low-volume user.

SATO

CX200TT
Thermal Transfer Printer

CX200DT
Direct Thermal Printer

Specifications:

Printing Method:
CX200TT: Thermal Transfer/Direct Thermal
CX200DT: Direct Thermal

Printing Speed:
Up to 3″ Per Second

Print Resolution:
203 dpi (8 dots/mm)

Print Area:
4.10″W x 14″L (104mm x 356mm)

Bar Code Symbology:
UPC-A/E, Code 39, Interleaved 2 of 5, EAN-8/13, UCC/EAN-128, MSI Code 128, Codabar, Code 93, Bookland, Postnet, Maxicode, PDF417
Ratio: 2:1, 3:1, 5:2, or individually adjustable bar widths
Height Programmable from 1 to 600 dots

Human Readable Fonts:
12 proportional and mono-spaced fonts including OCR-A and OCR-B, American and European characters, upper and lower case with descenders.

Graphic Support:
SATO Hex/binary format, .PCX format

Flexibility:
Rotation of text and bar codes in four 90˚ steps, character expansion horizontally and vertically in 12 steps, RAM storage for special characters, dot-addressable graphics and sequential numbering. Form overlay for high speed editing of complex formats.

Media:
Roll of fan fold die-cut labels and tags, synthetic or paper face stock.

Thickness:	.003″ to .007″ (0.08mm to 0.18mm)
Max. Roll Diameter:	5″ (127mm)
Roll Core Diameter:	1.5″ (38mm)
Minimum Size:	2″W x 0.375″L (51mm x 9.5mm)
Maximum Size:	4.65″W x 14″L (118mm x 356mm)

Memory:
512K Flash
512K RAM

Sensing:
Left justified see-through photo sensor for die cut, gap and notched media. Left justified reflective sensor for black Eye-mark. Sensor can be disabled for printing on continuous media.

Ribbon:
Width:	Up to 4.25″ (108mm)
Length:	459′ (140m) Wax
	416′ (127m) Wax/Resin, Resin
Core:	0.5″ (12mm) Internal Diameter

Interfaces:
Centronics Parallel
RS232C Serial (600-19,200 BPS)
(RTS/CTS, XON/XOFF)

External Connectors:
Parallel:	36-pin Amp
Serial:	DB-9F

Switches & Displays:
Switches:	LINE, FEED
LED Indicators:	On-Line, Status
Configuration:	Software

Dimensions:
10″D x 6.9″W x 6.6″H
(254mm x 175mm x 168mm)

Weight:
CX200TT:	3.6 lbs (1.63kg)
CX200DT:	3.1 lbs (1.41kg)

AC Power:
120V AC + 10% to -15% 50/60 Hz
230V AC + 10% to -15% 50/60 Hz
40W Power Supply Standard

Environment:
Operating:	41˚ to 104˚F (5˚ to 40˚C)
Storage:	0˚ to 122˚F (-20˚ to 50˚C)
25%-85% Non-Condensing RH
ESD Immunity: 8kV

Approvals:
FCC Class B, U/L, TUV, CE, CSA

Options:
Label Dispenser
Expanded Memory, 2 or 4 MB Factory Installed
RS232C Serial Printer Cable
80W Power Supply

Out of the box…and ready to go!
Complete with:
- User's Guide
- Programmer Guide
- Labeling Software
- Parallel Printer Cable
- Starter Roll of Media
- Starter Roll of Ribbon
- Power Supply